

APPLICATIONS

A shallow economy designed 7" wraparound LED luminaire available in either two or four foot lengths that is maintenance free and has a low initial cost. This series also delivers excellent brightness control and is suitable for individual or continuous run installations.

FEATURES & BENEFITS

- ◆ Low initial cost, maintenance free, excellent brightness control
- ◆ Design embossed ends are locked and secures to the housing
- ◆ Suitable for individual or continuous run installations
- ◆ Made in USA
- ◆ CRI 80+
- ◆ cETL_{us} Listed for damp locations

SPECIFICATIONS

Completely die formed from heavy gauge cold rolled steel. A crystal clear diffuser extruded from 100% virgin acrylic that will maintain it's color under normal conditions, indefinitely. Linear prisms on the interior side walls direct the light ceilingwards. The bottom is composed of an evenly spaced pattern of conical prisms yielding low brightness, glare-free, diffused light.



ORDERING DATA


EXAMPLE: 769-24LED28DMV40

769		Size		Width		LED		Wattage		Driver Type		Color Temp		Options	
Series	769	24	24 inch	Blank	Standard	Gear	LED	24"		DMV	Dimmable	30	3000K	WP	6' Whip 3 Wire
LED Premium Wrap	48	48 inch	W	Wide				23	23 Watts 2750 lumens	Multivolt	35	3500K	EM	10W, 1200 Lumen battery backup	
								28	28 Watts 3280 lumens	120-277VAC	40	4000K	EM7	7W, 840 Lumen battery backup	
								35	35 Watts 4330 lumens	0-10V	50	5000K	EM5	5W, 600 Lumen battery backup	
								24" wide		FIDMV	Factory Installed				
								32	32 Watts 3760 lumens	Dimming					
								48	48 Watts 5700 lumens	Multivolt					
								57	57 Watts 6500 lumens	120-277VAC					
								48"		0-10V					
								23	23 Watts 2930 lumens						
								35	35 Watts 4370 lumens						
								48	48 Watts 5750 lumens						
								56	56 Watts 6570 lumens						
								48" wide							
								65	65 Watts 8100 lumens						
								97	97 Watts 11500 lumens						
								114	114 Watts 13140 lumens						

Notes:
Consult factory for Step Dimming Options

END VIEWS

2 Rows LED Module
Slide on Socket Mount



Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆

8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE