

APPLICATIONS

Premium grade surface mounted wraparound luminaire with low brightness linear sides. For use in indoor applications where high efficiency, high performance and ease of installation is required. Ideal for retail stores, stairwells, utility areas, schools and public buildings.

FEATURES & BENEFITS

- ◆ P3 technology - Post Powder Paint > 90% reflectivity
- ◆ Corrosion and scratch resistant
- ◆ Smooth edges for easy handling
- ◆ 90 degree sides for easy side wiring
- ◆ Nominal 7 3/4" wraps
- ◆ Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- ◆ Diffuser self-aligns and hinges from either side for easy maintenance
- ◆ Single or continuous row mounting capability
- ◆ Every fixture individually tested.
- ◆ CRI 80+



SPECIFICATIONS

Housing and ends are die-formed from cold rolled steel. Finish is high reflectance P3 - Post Powder Paint. Diffuser hinges from either side in lift and shift manner and is self-centering.

SIZE: W x L x H in inches
7.75W x 48.0L x 4.5"H
7.75W x 96.0L x 4.5"H

MOUNTING: Surface or suspended

ORDERING DATA


EXAMPLE: 779-48LED32DMV40

779		LED							
Series	Size	Gear	Wattage + Lumens		Driver Type		Color Temp		Options
779	48 48 inches	LED	4 ft.		DMV	Dimmable	30	3000K	WP 6' Whip, 3 Wire
Premium 90°	96 96 inches		32	32 Watts 3450 lumens	Multivolt		35	3500K	EM 10W, 1200 Lumen battery backup
Wraparound			48	48 Watts 4800 lumens	120-277VAC		40	4000K	EM5 5W, 600 Lumen battery backup
			57	57 Watts 5700 lumens	0-10V		50	5000K	EM7 7W, 840 Lumen battery backup
			8 ft.		FIDMV	120-277VAC			
			48	38 Watts, 4800 lumens	Input				
			65	65 Watts, 7000 lumens	Factory installed				
			97	97 Watts, 9600 lumens	0-10V Dimming				
					SDMV	Step Dimming			
					120-277VAC				
					Multivolt				
					100%-40%				

*Consult for triac dimming



FIXTURE CROSS SECTION VIEW



FIXTURE BACK PLAN VIEW

