

### APPLICATIONS

The LED Crown series provides general illumination in residential, institutional and commercial interiors. Ideal for use in kitchens, office, utility areas or closets. Crown molding frame available in oak or white finish. Bracket and single screw frame.

### FEATURES & BENEFITS

- ◆ Surface or pendant mounting
- ◆ Beautiful matte lens for even light distribution
- ◆ Highest quality long life LED
- ◆ Double the life expectancy of fluorescent technology
- ◆ <sup>c</sup>ETL<sub>US</sub> Listed



### SPECIFICATIONS

Specially formed plastic diffuser produces flawless light source with even illumination on all sides and no distracting dark spots. Invisible hanging clips permit removal of lens from either side.

### ORDERING DATA

**EXAMPLE: CWN24MW-LED48DMVWH40**

CWN		MW		LED	Wattage/Lumens		Driver	Finish		Color Temp	
Series	Size	Lens	Gear								
<b>CWN</b>	<b>14</b> 1x4 <b>22</b> 2x2 <b>24</b> 2x4	<b>MW</b> Matte White Acrylic	<b>LED</b>		<b>1x4</b>		<b>DMV</b> Dimming 120-277VAC Multivolt 0-10V	<b>WH</b> White <b>GO</b> Golden Oak* <b>BW</b> Bleached White*	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K <b>50</b> 5000K		
					<b>2x2</b>		<b>SDMV</b> Step Dimming 120-277VAC 100%-40%	*GO+BW Special Order			
					<b>2x4</b>		*Consult for triac dimming				
					<b>32</b> 32 Watts 3450 Lumens						
					<b>48</b> 48 Watts 4800 Lumens						
					<b>57</b> 57 Watts 5400 Lumens						
					<b>72</b> 72 Watts 7000 Lumens						
					<b>24</b> 24 Watts 2400 Lumens						
					<b>28</b> 28 Watts 2700 Lumens						
					<b>35</b> 35 Watts 3200 Lumens						
					<b>32</b> 32 Watts 3450 Lumens						
					<b>48</b> 48 Watts 4800 Lumens						
					<b>57</b> 57 Watts 5400 Lumens						
					<b>72</b> 72 Watts 7000 Lumens						

### DIMENSIONS

#### W x L x H in inches

25.0W x 25.0L x 4.125Dp  
11.5W x 48.875L x 4.125Dp  
16.75W x 48.875L x 4.125Dp

Dimensions and specifications subject to change without notice.



◆ 800-444-WATT ◆ www.mobern.com ◆

8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#

JOB NAME

TYPE