

#### APPLICATIONS

Mobern introduces LED low profile rectilinear lighting that can be pendant or wall mounted individually. Ideal for general lighting applications in both commercial and residential applications for circulation spaces, high impact areas and kitchen islands and home offices. The versatility and clean styling makes this an ideal choice in many applications.

#### FEATURES & BENEFITS

- ◆ Size: (W x L x H in inches)  
4ft. - 7.60" x 48.0" x 1.9"  
8ft. - 7.60" x 96.0" x 1.9"
- ◆ Mount with 4' adjustable cable (2 for 4' unit or 8' unit, included)  
Consult factory for longer cables.



**Two Lumen Packages**  
Available in Standard output and High output lumen packages

#### ORDERING DATA

EXAMPLE: LLPMW48LED24DMVWH30

LL		LED									
<b>Series</b>	LL	<b>Length</b>	48 48" 96 96"	<b>Gear</b>	LED	<b>Driver</b>	DMV 0-10V Dimming 120-277V Multi-volt	<b>Color Temp</b>	30 3000K 35 3500K 40 4000K 50 5000K		
<b>Mounting</b>	P Low Profile Pendant W Low Profile Wall Mount	<b>Lens</b>	MW White Lens FR Frosted Lens			<b>Wattage &amp; Lumens</b>	<u>4 Ft. Up or Down Only</u> 24 24 Watts / 2400 Lumens 48 48 Watts / 4800 Lumens <u>4 Ft. Uplight &amp; Downlight</u> 36 36 Watts / 3600 Lumens 54 54 Watts / 5400 Lumens <u>8 Ft. Up or Down Only</u> 48 48 Watts / 4800 Lumens 96 96 Watts / 9600 Lumens <u>8 Ft. Uplight &amp; Downlight</u> 72 72 Watts / 7200 Lumens 108 108 Watts / 10800 Lumens	<b>Finish</b>	WH White SL Silver RD Red IN Iron BK Black	<b>Cable Kit</b>	(blank) 4ft Cable kit w/ 3 wire cord HC402 12 ft cable kit w/3 wire cord HC401-5W 4 ft cable kit w/ 5 wire cord HC402-5W 12 ft cable kit w/5 wire cord
		<b>LED Module Distribution</b>	(blank) Downlight only U Uplight only 1U2D 1/3 Uplight 2/3 Downlight 2U1D 2/3 uplight 1/3 downlight						<b>Options</b>	EM 10 Watt 1200 Lumens ** Battery Backup EM5 5 Watt 600 Lumens ** Battery Backup EM7 7 Watt 840 Lumens ** Battery Backup **Estimated Lumens	

\*Consult for more options

Dimensions and specifications subject to change without notice.

