

### FEATURES & BENEFITS

- ◆ Dimmable 120V input voltage, 50/60Hz
- ◆ Ambient operating temperature -40°C (-40°F) to +50°C (122°F)
- ◆ Estimated 50,000 Hrs L<sub>70</sub>
- ◆ Molded of durable non-corrosive UV resistant resins
- ◆ Acrylic diffuser
- ◆ Post tops fit most 3 inch diameter posts (not included)
- ◆ UL Listed for wet locations
- ◆ Energy Star Listed in wall and long tail versions




### ORDERING DATA


EXAMPLE: MHTPWLED12D120WH30

MHT	LED	12	D120					
Series	Mount	Lens	Gear	Wattage / Lumens	Driver	Finish	Color Temp	Options
MHT	<b>P</b> Post Top <b>W</b> Wall Mount <b>L</b> Wall Mount Long Tail <b>S</b> Wall Mount Short Tail	<b>CL</b> Clear <b>WH</b> White	<b>LED</b>	<b>12</b> 13 Watts 1000 Lumens Estimated from LED Source	<b>D120</b> 120VAC Triac Dimmable	<b>WH</b> White <b>BK</b> Black	<b>30</b> 3000K <b>40</b> 4000K	<b>PC</b> Photocell* *Photocell Not Available on Post Top


MHTW




MHTL



MHTS



MHTP



Dimensions and specifications subject to change without notice.

