

**APPLICATIONS**

The **MIMDCOWPK** Decorative Full Cut-off Wall Pack is ideal for security, accent and perimeter lighting. Applications include entrance ways, garages, and commercial buildings.

**FEATURES & BENEFITS**

- ◆ Heavy Duty Die Cast Aluminum Housing
- ◆ Tempered Glass Lens
- ◆ Die Cast Hinged Front & Rear Housings, Gasket
- ◆ Coin Plugs on Sides and Back
- ◆ Built-In Template for Mounting to Electrical Box
- ◆ Chromate Conversion Coating
- ◆ Textured Bronze Finish
- ◆ Two Piece Hinged Aluminum Reflector
- ◆ Meets Local "Dark Sky" Requirements
- ◆ Lamps are included
- ◆ cETL Listed (wet location)

**SPECIFICATIONS**

Housing is die-cast aluminum body with chromate conversion coating with textured bronze finish. Heat and shock resistant borosilicate glass refractor permanently bonded to lens frame. Lens is a clear, tempered glass with aluminum reflector. Gasket is a high temperature silicone. Back plate features 1/2" and 3/4" threaded knockouts cast-in for alignment with all standard recessed boxes. Listed by and bears cETL label.



**ORDERING DATA**

EXAMPLE: MIMDCOWPK70MHPSQVPC2

MIMDCOWPK

Series	Lamp	Wattage	Ballast Type	Options
<b>MIMDCOWPK</b> Decorative Cut-off Wall Pack	<b>Blank</b> HID Lamp <b>1</b> 1 CFL Lamp <b>2</b> 2 CFL Lamp	<b>26</b> 26W CFL <b>32</b> 32W CFL <b>42</b> 42WCFL <b>50HPS</b> HPS <b>70HPS</b> HPS <b>150HPS</b> HPS <b>70MHPS</b> MHPS <b>100MHPS</b> MHPS <b>150MHPS</b> MHPS <b>175MHPS</b> MHPS	<b>ELPL</b> CFL MV 120 - 277V <b>QV</b> 120, 208, 240, 277V <b>120</b> 120V <b>277</b> 277V <b>480</b> 480V	<b>BK</b> Black Housing <b>WH</b> White Housing <b>B1</b> Emergency Battery Pak <b>PC1</b> Photo Cell, 120V <b>PC2</b> Photo Cell, 208-277V

MIMDCOWPK SERIES ORDER INFORMATION	
<b>HIGH PRESSURE SODIUM</b>	
MIMDCOWPK70HPSQV	HPS70-120V
MIMDCOWPK70HPS480	HPS70-480V
MIMDCOWPK100HPSQV	HPS100-120V
MIMDCOWPK100HPS480	HPS100-480V
MIMDCOWPK150HPSQV	HPS150-QV
MIMDCOWPK150HPS480	HPS150-480V
<b>METAL HALIDE</b>	
MIMDCOWPK50MHPSQV	MH50-PS-QV
MIMDCOWPK70MHPSQV	MH70-PS-QV
MIMDCOWPK100MHPSQV	MH100-PS-QV
MIMDCOWPK100MHPS480	MH100-PS-480V
MIMDCOWPK150MHPSQV	MH150-PS-QV
MIMDCOWPK150MHPS480	MH150-PS-480V
MIMDCOWPK175MHPSQV	MH175-PS-QV
MIMDCOWPK175MHPS480	MH175-PS-480V
PS = Pulse Start QV (QUAD VOLT)=120, 208, 240 and 277 Volt	
<b>COMPACT FLUORESCENT</b>	
PMIMDCOWPK126EPL	CF 1 Lamp 26W MV
PMIMDCOWPK132EPL	CF 1 Lamp 32W MV
PMIMDCOWPK142EPL	CF 1 Lamp 42W MV
PMIMDCOWPK213EPL	CF 2 Lamp 13W MV
PMIMDCOWPK226EPL	CF 2 Lamp 26W MV
PMIMDCOWPK232EPL	CF 2 Lamp 32W MV
PMIMDCOWPK242EPL	CF 2 Lamp 42W MV
PL= Compact Fluorescent, Electronic, MultiVolt (DT)	

Dimensions and specifications subject to change without notice.

CAT#	
JOB NAME	TYPE

