

APPLICATIONS

High quality recessed lensed troffer has an almost infinite use of applications. Ideal applications include commercial offices, schools, hospitals, retail locations just to name a few.

FEATURES & BENEFITS

- ◆ Min 80 CRI
- ◆ 120° beam angle
- ◆ Operating temperature of -20°C (-4°F) - 45°C (113°F)
- ◆ 5 year warranty
- ◆ Easily installs into T-Bar ceilings
- ◆ Galvanized back cover
- ◆ 35,000 hours of life L70
- ◆ Removable white lens
- ◆ IC rated for direct contact with insulation

DIMENSIONS (LxWxH)

2x2 - 23.8" x 23.8" x 3.1"
2x4 - 47.8" x 23.8" x 3.1"

SPECIFICATIONS

Housing is sheet steel secured to frame by clips. 2x2 has 81 LED chips. 2x4 has 90 LED chips. Driver cover snaps easily into place eliminating the need for tools when accessing the driver. Lens is secured to groove of frame.



ORDERING DATA

EXAMPLE: RT22LED24DMV40

RT	LF	DMV	40
Series	Size	Wattage / Lumens	Driver Type
RT	22 2 x 2 24 2 x 4	24 24W 3000 Lumens 40 40W 5000 Lumens	DMV 0-10V dimmable 120-277V AC
			Color Temp 40 4000K

Dimensions and specifications subject to change without notice.

CAT#			
JOB NAME		TYPE	