

JOB NAME:
CAT#:
TYPE:

APPLICATIONS

Low profile dual basket is ideal for shallow plenum spaces. Specification grade, direct/indirect dual diffuser luminaire proves smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matter surfaces provide a softened "sky light" appearance to the modern office environment.

- Direct/indirect mimics "sky light" appearance
- Matte white reflective surfaces for soft, uniform light distribution
- Over 80% efficiency when used with optional ribbed acrylic diffuser
- Recessed dual perforated diffuser with acrylic overlay
- For use in recessed inverted T-Bar or grid ceilings
- UL Listed for damp location

Housing is die-formed and embossed code gauge steel. Luminaire body finish is high reflectance baked white enamel, with matte white reflectors. Wiring knockouts are provided on the back of housing. Diffusers are perforated to maintain even brightness, and provided with an internal acrylic overlay to obscure lamps.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance. EZLED fixtures are UL Listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

DIMENSIONS

2x2 - 23.68"W x 23.68"L x 3.25"D

2x4 - 23.68"W x 47.67"L x 3.25"D

ORDERING

EXAMPLE: RDISD 22 2 17 PF LEDL7W 830 KEY WP

RDISD

1. SERIES	2. SIZE	3. LAMP #	3. LAMP TYPE	4. DIFFUSER	5. WATTAGE/LUMENS	6. COLOR TEMP
RDISD	22 2x2	2 2 Lamps	17 24" T8	PF Perforated basket	T8 Options 2 ft.	
	24 2x4	4 4 Lamps	32 48" T8	RL Ribbed acrylic		
			54 46" T5HO		T8 Options 4 ft.	
					LEDL12W 12.5 Watts 1750 Lumens Keystone	830 3000K
					LLEDL15W 15 Watts 1740 Lumens	835 3500K
					LEDL18W* 18 Watts 2500 Lumens	840 4000K
					T5 Options	
					LEDL25W 25 Watts 3300 Lumens	850 5000K
7. LAMP BRAND		8. OPTIONS				
Blank	House Brand Lamp (Savegreen)	WP	6' whip, 3 wire			
KEY	Keystone Brand	INV5	5W Integrated Inverter			
JAM	James Brand**					
		** Special Order				



FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70>50,000 hrs.
- Operating temperature: -20°C to 50°C
- Color temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast.
- Environmentally friendly, no mercury used.
- UL Classified
- Min CRI 80
- 5 year warranty

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.



Dimensions and specifications subject to change without notice.

Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.