



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Premium grade recessed troffer dish with a center basket that provides direct/indirect light with modern styling and high visual comfort. For use in commercial and industrial buildings where low glare, high quality, design and ease of installation are required.

Housing is a die-formed from cold rolled steel. P3 - Post Powder Paint finish in a matte white. Indirect reflectors are precision formed and contoured to provide soft indirect illumination while maintaining high efficiency and wide uniform lighting distribution. Die-formed steel basket is perforated for direct illumination with a translucent opal white acrylic overlay diffuser for visual comfort. Perforated basket flexes over mounting studs on housing for easy installation. Wiring access plate or knockouts are provided on back of housing for flexible conduit attachment. Hole provided for chain mounting support to building structure. Surface mount options are available.



FEATURES & BENEFITS

- Contemporary shallow design
- Single basket shaped perforated metal shield
- Translucent opal white acrylic diffuser overlay
- Clean appearance with no exposed fasteners
- Solid metal basket available for indirect lighting
- Min CRI 82
- IC Rated
- c_{ETL}_{US} listed for damp location up to 67 watts





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: RDICB 22 LED 24 DMV 30 EM WP

RDICB		LED				
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER	6. LENS	7. COLOR TEMP
RDICB	22 2x2 24 2x4	LED	2x2 24 24 Watts 2160 Lumens 28 28 Watts 2160 Lumens 35 35 Watts 2720 Lumens 2x4 32 32 Watts 2760 Lumens 48 48 Watts 3840 Lumens 57 57 Watts 4320 Lumens 72 72 Watts 5600 Lumens	DMV 120-277V Multivolt 0-10V Dimmable	PF Perforated Lens	30 3000K 35 3500K 40 4000K 50 5000K

8. EMERGENCY(O)¹

- EM** Emergency Battery Pack 10W ~ 1700 lumens
- EM5** Emergency Battery Pack 5W ~ 850 Lumens

9. CORD(O)¹

- WP** 6' 3 Wire Flexible Conduit

Notes:
¹(O) is optional

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

