



Premium grade strip fixture. Available in a compact one light configuration especially suited for areas with minimal space requirements such as cove lighting, store fixture, signage, under cabinets, closets, display cases, vending machines and confined areas requiring illumination and ease of installation.

- · Standard finish is white
- Optional white reflectors available
- · Continuous row mounting capability
- Shallow design
- UL listed for damp location

#### CONSTRUCTION

Housing is die and brake formed from cold rolled steel. One piece folded construction. Finish is high reflectance baked white enamel. End caps may be butted together for continuous row mounting. Knockouts are provided for flexible conduit attachment.

### SIZE W x L x H in inches

1.62 x 24 x 1.62 1.62 x 48 x 1.62 Fixture length = lamp length



The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

## **Lamp Specifications**

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www. savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- · Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- · Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

### **Optional Dimming**


The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver.

### **Emergency Options**

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

## **ORDERING DATA**

# **EXAMPLE:41-117LEDL15W840**



\*Premium lamp option













Dimensions and specifications subject to change without notice.

800-444-WATT ◆ www.mobern.com ◆ 8200 Stayton Dr., Ste. 500, Jessup, MD 20794

CAT#
JOB NAME

TYPE