

JOB NAME:
CAT#:
TYPE:

APPLICATIONS

Decorative surface mounted luminaire provides unique floating cloud appearance. Ideal for kitchens, hallways, lobbies and areas requiring diffused soft light.

- P3 Technology - Post Powder Paint
- >90% reflectivity
- Corrosion and scratch resistant
- Smooth edges for easy handling
- Flat surfaces and square corners provide a contemporary styling surface, stem or chain mountable
- White opal acrylic wraparound diffuser
- Diffuser self-aligns and hinges from either side for easy maintenance and re-lamping
- Black finish optional
- Clean appearance with no exposed fasteners
- High impact resistant "Indestruct-A-Puff"
- UL listed for damp location

Housing is die-formed and spot welded, cold rolled steel. Finish is high reflectance white with P3 - Post Powder Paint. Diffuser hinges from either side in a lift and shift manner and is self-centering. Mounts over electrical junction box. Mounting holes are provided within offset to prevent distortion of housing when tightening mounting fasteners. The soft matte opal white acrylic diffusers provide even illumination.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM kit. See emergency options and specs at www.mobern.com/EZLEDEmergency.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).



FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

DIMENSIONS

SIZE W x L x D in inches

11.75 x 26.5 x 6

11.75 x 50.5 x 6

17 x 26.5 x 6

17 x 50.5 x 6



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: C 9 2 17 LEDL7W 830 WP

C

1. SERIES	2. SIZE	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. COLOR TEMP
C Cloud	9 11.75"	2 2 Lamps*	17 24" T8	<u>2 ft.</u>	830 3000K
	15 17"	4 4 Lamps**	32 48" T8	LEDL7W 7 Watts 950 Lumens <u>Keystone</u>	835 3500K
		*C9 Only ** C15 only		LEDL9W 9 Watts 1050 Lumens <u>4 ft.</u>	840 4000K
				LEDL12W 12.5 Watts 1750 Lumens	850 5000K
				LEDL15W 15 Watts 1740 Lumens	
				LEDL18W* 18 Watts 2500 Lumens*	

*Premium lamp option

7. LAMP BRAND	8. WHIP
Blank House Brand	WP 6' Whip, 3 Wire
KEY Keystone Brand	
JAM James Brand**	

** Special order

Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.