



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Economically designed narrow wraparound provides reliable and efficient lighting. Ideal for use in indoor applications such as homes, modular homes, mobile homes, stores and public buildings where low glare and ease of installation is required.

- Nominal 8" width with a shallow design
- Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- Diffuser self-aligns and hinges from either side for easy maintenance
- Single or continuous row mounting capability
- Surface, stem or chain mountable
- UL listed for damp location

Housing and ends are die-formed and embossed from cold rolled steel. Finish is high reflectance baked white enamel. Inspection knockouts provided for mounting to junction box. Diffuser hinges from either side in a lift and shift manner and is self-centering. End caps may be butted together for continuous row mounting. Knockouts are provided for stem mounting.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Dimensions and specifications subject to change without notice.

FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty



Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/EZLEDEmergency.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

DIMENSIONS

SIZE W x L x H in inches (mm)

- 2 lamp - 7.625W x 24L x 3H - 2ft fixture
- 7.625W x 48L x 3H - 4ft fixture
- 3 or 4 lamp - 13W x 48L x 3H - 4ft fixture



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: 769 2 17 LED L7W 830 WP INV5

769

LED

1. SERIES	2. # OF LAMPS	3. LAMP TYPE	4. GEAR	5. LAMP WATTAGE	6. LENS	7. COLOR TEMP
769	2 2 Lamps	17 24 inch T8	LED	T8 OPTIONS	Blank Clear	830 3000K
Economy	3 3 Lamps	32 48" T8		2 ft.	Prismatic	835 3500K
Wraparound	4 4 Lamps	54* 46 inch T5HO		L7W 7 Watts 950 Lumens <u>Keystone</u>	FR Frosted	840 4000K
		*Only available in 840 & 850		L9W 9 Watts 1050 Lumens 4 ft.		850 5000K
				L12W 12.5 Watts 1750 Lumens <u>Keystone</u>		
				15W 15 Watts 1740 Lumens		
				L18W* 18 Watts 2500 Lumens* T5 Options		
				L25W 25 Watts 3300 Lumens		

*Premium lamp option

8. LAMP BRAND	9. WHIP	10. INVERTER
Blank House Brand	WP 6' Whip, 3 Wire	INV5 5W Integrated Inverter
KEY Keystone Brand		
JAM James Brand**		

** Special order

Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.