



**JOB NAME:**

**CAT#:**

**TYPE:**

**FEATURES & BENEFITS**

- Input Voltage: 120VAC, 56/60Hz
- Input Current: 150mA ± 10%
- L<sub>70</sub> >36000 hrs
- Ambient Temperature: -20°C to +50°C
- Min CRI 80
- CCT: 4000K (Consult for other color temperatures)
- Suitable for damp locations
- Fixture is linkable and can be hard wired or use power cord.
- Fixture comes with power cord, knock-connector and joiner cable.
- Fixture comes with rocker switch installed



**DIMENSIONS**

- 9”L x 5”W x 1”H
- 12”L x 5”W x 1”H
- 18”L x 5”W x 1”H
- 24”L x 5”W x 1”H
- 33”L x 5”W x 1”H
- 42”L x 5”W x 1”H

**ORDERING**

EXAMPLE: MLUC 9 L 5W E120 40

**MLUC**

1. SERIES	2. SIZE	3. ROW CONNECTION	4. WATTAGE/LUMENS	5. DRIVER	6. COLOR TEMP
<b>MLUC</b>	<b>9</b> 9”	<b>L</b> Linkable	<b>9 in.</b>	<b>D120</b> Electronic 120V only	<b>MCT</b> 3000K, 3500K, 4000K Color selectable
LED Under	<b>12</b> 12”		<b>5W</b> 5 Watts 250 Lumens		
Cabinet Fixture	<b>18</b> 18”		<b>12 in.</b>		
	<b>24</b> 24”		<b>6W</b> 6 Watts 300 Lumens		
	<b>33</b> 33”		<b>18 in.</b>		
	<b>42</b> 42”		<b>9W</b> 9 Watts 450 Lumens		
			<b>24 in.</b>		
			<b>11W</b> 11 Watts 550 Lumens		
			<b>33 in.</b>		
			<b>13W</b> 13 Watts 650 Lumens		
			<b>42 in.</b>		
			<b>16W</b> 16 Watts 900 Lumens		

**NOTE:** Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.



JOB NAME:

CAT#:

TYPE:

**ACCESSORIES**



**Knock-out Connector**



**39" Power Cord**



**6" Joiner Cable**

**DIMENSIONS**

