



JOB NAME: CAT#: TYPE:

#### **FEATURES & BENEFITS**

- Surface mounts to existing junction box or new construction with two screws
- Slim close-to-ceiling LED arrays providing 10W with 660 lumens and 15W with 1000 lumens at 3000K color temperature
- CTCS and CTCR Series dims to 10% with standard dimmers<sup>1</sup>
- cETL<sub>us</sub> listed for wet locations
- White or brushed nickel finish





Dimensions In Inches						
CTCR5LED10	5.5"D x 0.625"H, 660 Lumens					
CTCR7LED15	7.0"D x 0.625"H, 1000 Lumens					
CTCS5LED10	6.28"L x 6.28"W x 0.625"H, 660 Lumens					
CTCS7LED15	8.0"L x 8.0"W x 0.625"H, 1000 Lumens					



#### **ORDERING (ROUND)**

EXAMPLE: CTCR 5 LED 10 D120 WH 30

CTCR			LED								
1. SERIES	2. SIZE		3. GEAR	4. WATTAGE		5. DRIVER		6. FINISH		7. COLOR TEMP	
CTCR	5	5"	LED	10	10 Watts	D120	120V Triac	WH	White	30	3000K
Round							Dimmable	BN	Brushed Nickel		

## **ORDERING (ROUND)**

EXAMPLE: CTCR 7 LED 15 D120 WH 30

CICR			LED								
1. SERIES	2. SIZE		3. GEAR	4. WATTAGE		5. DRIVER		6. FINISH		7. COLOR TEMP	
CTCR	7	7"	LED	15	15 Watts	D120	120V Triac	WH	White	30	3000K
Round							Dimmable	BN	Brushed Nickel		

**NOTE:** Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.







<sup>&</sup>lt;sup>1</sup> Triac Based (forward phase control or leading edge dimmers)





CAT#: **TYPE: JOB NAME:** 

## **ORDERING (SQUARE)**

EXAMPLE: CTCS 5 LED 10 D120 WH 30

**CTCS LED** 

1. SERIES 4. WATTAGE 5. DRIVER 6. FINISH 7. COLOR TEMP 2. SIZE 3. GEAR

**CTCS 5** 5" LED **10** 10 Watts **D120** 120V Triac WH White **30** 3000K Dimmable Square

**BN** Brushed Nickel

### **ORDERING (SQUARE)**

EXAMPLE: CTCS 7 LED 15 D120 WH 30

**LED CTCS** 1. SERIES 7. COLOR TEMP 2. SIZE 3. GEAR 4. WATTAGE 5. DRIVER 6. FINISH

**WH** White D120 120V Triac **30** 3000K **7** 7" **CTCS** LED

**15** 15 Watts Square Dimmable **BN** Brushed Nickel

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.











JOB NAME: CAT#: TYPE:

# **DIMENSIONS & DRAWINGS**

# **CTCR**



# **CTCS**







