

JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Premium grade enclosed and gasketed fixture. For use in both indoor and outdoor applications where dust and water resistance is required. Ideal for marinas, parking garages, barns, canopies, car washes, poultry farms, agricultural applications and other areas susceptible to corrosive conditions

High quality enclosed fiberglass fixture features a unique continuous poured gasket which completely fills channel for maximum seal integrity. Diffuser is held in place with polycarbonate retaining latches. Stainless steel latches are recommended for the following applications: agriculture, car washes, food processing and swimming pools. Hole is 7/8" diameter and is provided with a plastic plug on one end for conduit attachment. Offset mounting pads which keeps luminaire level and slightly off of mounting surface are formed within the housing. Highly reflective coated interior surface improves efficiency. Standard diffuser is high impact acrylic with smooth finish for high efficiency.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty



Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/EZLEDEmergency.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

DIMENSIONS

Dimensions	Length	Width
2 ft.	27.68"	8.77"
4 ft.	51.85"	8.77"
8 ft.	100.00"	8.77"

Fixture Depth Options	
SSC + SSF	4.27"
RF + RC	4.38"
SC + SF	5.75"

Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: VW 117 LEDL7W RF 830 INV5

VW

1. SERIES	2. # OF LAMPS	3. LAMP TYPE	5. LAMP WATTAGE	6. LENS	7. COLOR TEMP
VW	1 1 Lamp	17 24 inch T8	T8 OPTIONS 2 ft.	RF Ribbed frosted RC Ribbed clear SF Smooth frosted* SC Smooth clear* SSF Shallow, smoot frosted SSC Smooth white .100 thick lens	830 3000K 835 3500K 840 4000K 850 5000K
	2 2 Lamps	32 48 inch T8			
	3 3 Lamps	32TAN 2-48" T8 Tandem 54* 46 inch T5HO	LEDL7W 7 Watts 950 Lumens <u>Keystone</u>		
		*Only available in 840 & 850	LEDL9W 9 Watts 1050 Lumens 4 ft. and 8 ft. <u>Keystone</u>		
			LEDL12W 12.5 Watts 1750 Lumens <u>Keystone</u>	*Not available in polycarbonate	
			LEDL15W 15 Watts 1740 Lumens		
			LEDL18W* 18 Watts 2500 Lumens T5 Options		
			LEDL25W 25 Watts 3300 Lumens		

*Premium lamp option

8. LAMP BRAND	9. INVERTER
Blank House Brand	INV5 5W Integrated Inverter
KEY Keystone Brand	
JAM James Brand**	

** Special order

ACCESSORIES

Clips and Hangers Accessories



- Replacement white latch (sold as each)
- H123 - 2 Ft., 4 Ft. & 8 Ft.*



- Stainless steel latch kit set
- H126 - 2 Ft. & 4 Ft.
- H127 - 8 Ft.



- Stainless steel mounting bracket
- Mounts fixture at 45° angle from wall or ceiling
- VW-MB2L-2PK-45DEG



- Stainless steel mounting bracket w/bail
- VW-MB2L-B-2PK (Recommended for cable hanging)



- Stainless steel mounting bracket
- VW-MB2L-2PK

Note:

* To replace latches on entire fixture order 6 latches for 2 Ft., 8 latches for 4 Ft., and 14 latches for 8 Ft.

Lumens are subject to a tolerance of ±10% and not relevant to RGB Input wattage can vary depending on options
Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.