

JOB NAME: CAT#: TYPE:

ILLUMINATION

• Ultra bright, energy efficient, long life red or green LEDs

ELECTRICAL

- Dual 120/277 voltage
- · Offers 11W of remote capacity standard
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge
- · 6V maintenance-free, rechargeable sealed lead acid battery
- Internal solid-state transfer switch automatically connects the internal battery to the LED board and remote lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.



MOUNTING

- EZ-snap mounting canopy included for top or end mount
- · Universal knockout pattern on back plate for wall mount


HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish
- EZ snap-out chevron directional indicators

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for 2 years
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Meets CSA C22.2 No. 141-02 requirements for unit equipment
- UL listed for damp locations (20°C-50°C)
- Certified to CEC under Title 20 regulations

DIMENSIONS



Dimensions and specifications subject to change without notice.





EZXTEU-RCRemote Capable Thermoplastic Exit Sign

JOB NAME:	CAT#:	TYPE:

ORDERING

EXAMPLE: EZXTEU 2 R W EM RC

EZXTEU

1. MODEL	2. # OF FACES		3. LETTER COLOR		4. HO	4. HOUSING COLOR		5. BATTERY		6. REMOTE CAPACITY	
EZXTEU	2	Universal/ Single/Double Face	R G	Red Green	W B	White Black	EM	Battery Backup	RC	Remote Capable	

7. HEATING (O)1

HTR Internal Heater

Notes:

¹(O) is optional





Dimensions and specifications subject to change without notice.