

JOB NAME:

CAT#:

TYPE:

ILLUMINATION

- Long lasting, efficient ultra bright white LED light strip
- 3.1 watts (24 LEDs x 0.13 watts) per light strip
- Patent-pending high performance, smooth, chrome plated, metallized reflector with acrylic UV stabilized lens for optimal light distribution
- Long life ultra-bright, energy efficient red or green LED exit sign illumination

ELECTRICAL

- Dual 120/277 voltage
- Unique bi-color LED indicator alerts occupant on battery condition (greennormal, red-check battery)
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 3.6V long life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to red/green LED board and the white LED light strip for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

• Universal knockout pattern on back plate for wall mount


HOUSING

- Patented specification-grade, low profile thin plastic design is ideal for low level applications
- Injection-molded, engineering grade, 5VA flame retardant high-impact resistant, thermoplastic in white or black finish
- EZ snap-out chevron directional indicators

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for 5 years
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL listed for damp locations (0°C-50°C)
- Certified to CEC under Title 20 regulations

DIMENSIONS



Dimensions and specifications subject to change without notice.



REVISED 12/04/2021

PAGE 1/2



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: LCTXTEU1RW

LCTXTEU

1. MODEL	2. # OF FACES		3. LETTER COLOR		4. HOUSING COLOR	
LCTXTEU	1	Single Face	R	Red	w	White
			G	Green	В	Black



Dimensions and specifications subject to change without notice.