

JOB NAME: CAT#: TYPE:


APPLICATIONS


A cloud of illumination from a contemporary shallow acrylic diffuser provides soft and even light for the home or office. Ideal for kitchens, hallways, lobbies and any area that would aesthetically benefit from soft and even illumination.


FEATURES & BENEFITS

- L₇₀ > 50,000 hrs.
- White opal acrylic diffuser
- Diffuser self-aligns and hinges from either side when maintenance is required
- Min CRI 82
- Clean appearance with no exposed fasteners
- Each fixture is individually tested
- ETL Listed for damp locations

DIMENSIONS







C15











JOB NAME: CAT#: TYPE:

ORDERING

EXAMPLE: C15 24 LED 32 DMV 30

1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER	6. COLOR TEMP	7. EMERGENCY
С	1524 17"W x 26.5" L 2624 26.5"W x 26.5"	LED	 C15-24 32 Watts 2600 lumens 48 Watts 3500 lumens C26-24 24 Watts 1800 lumens 	DMV 120-277V Multivolt 0-10V Dimmable D120 Triac Dimming 120VAC	30 3000K 35 3500K 40 4000K 50 5000K	EM5 5W Emergency B/U EM 10W Emergency B/U
	948 11.75"W x 50.5' 1548 17"W x 50.5" L		 36 36 watts 2900 lumens C9-48 32 32 watts 2600 lumens 48 watts 3500 lumens C15-48 57 watts 4200 lumens 72 watts 5400 lumens 			

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.





