



JOB NAME:

CAT#:

TYPE:

### APPLICATIONS

The CER is a round, commercial-grade wall or ceiling mounted fixture available in black or white, with frosted lens. Available with plain, grill, or eyelid lenses. Ideal for nautical applications. Wet location.

### FEATURES & BENEFITS


- Available in black or white with frosted lenses
- Fade and rust resistant composite constructions
- High power factor
- cUL<sub>US</sub> listed for wet locations
- 3 year warranty for MV and INC w/ lamp
- 5 year warranty for LED dimmable 120V Ambient temperature -40°C - +40°C
- Wall or ceiling mount



**FE361**




**FE362**




**FE363**

### DIMENSIONS


**FE361**




**HCMT: 5 1/8"**




**FE362**




**HCMT: 5 1/8"**



**FE363**



**HCMT: 5 1/8"**





JOB NAME:

CAT#:

TYPE:

**ORDERING**

EXAMPLE: FE361 LE800 W W C P

**LE800**

1. STYLE	2. LIGHT SOURCE	3. COLOR TEMP	4. BODY	5. DIFFUSER	6. OPTIONS <sup>1</sup>
<b>FE361</b> Plain Lens <b>FE362</b> Eyelid Lens <b>FE363</b> Grill Lens	<b>LE800</b> 13W Power Input, CRI 80 >88 Lumens Per Watt (TYP)	<b>W</b> 3000K <b>C</b> 4000K	<b>W</b> White <b>B</b> Black	<b>F</b> Frosted	<b>P</b> Photocell*

**ORDERING (INCANDESCENT)**

EXAMPLE: FE361 I75 W C LWE

**I75**

1. STYLE	2. LIGHT SOURCE	3. BODY	4. DIFFUSER	5. LAMPING
<b>FE361</b> Plain Lens <b>FE362</b> Eyelid Lens <b>FE363</b> Grill Lens	<b>I75</b> 1 X 75W Max	<b>W</b> White <b>B</b> Black	<b>C</b> Clear Flemish	<b>LWE</b> A19/E26, 3000K <b>LCE</b> A19/E26, 4000K

**Notes:**

<sup>1</sup>Photocell not available for FB255 style

