



JOB NAME:

CAT#:

TYPE:

APPLICATIONS


Specification grade, modular linear lighting luminaire in a geometric 6 inch shape. For use in indoor applications where individual or continuous lighting is desired for general or perimeter lighting applications. The L66 LED Series is available in surface, pendant (suspended) or recessed. Recessed L66 Series are available for T-bar installation without a flange or for flanged construction for sheetrock installation. Pendant and surface mount configurations allow direct light only. Pendant mounted fixtures can be used with cable kits or rigid stem kits specified separately. Surface and pendant fixtures can be painted in a variety of finishes for the right look for your application.

Housing is die-formed and welded of heavy gauge cold rolled steel. Knockouts on the ends allow continuous wireway mounting. Fixtures can be hung in various types of recessed ceilings. Leveling lugs are available to support regular recess units. All metal parts are cleaned and treated with a three-stage phosphate coating. These are electrostatically sprayed with high quality white baking enamel providing a minimum of 67% reflectivity.

FEATURES & BENEFITS

- 6.0W x 6.0H (See Dimensions)
- Various lenses lie on the side flanges
- 6' and 8' units have a steel mullion to join two individual diffusers
- Recessed versions are all IC Rated (L66R,L66RF,L66RR)
- cETL_{us} listed

DIMENSIONS



Uplight & Downlight



Continuous Run End



Wall/Pendant Mount

Dimensions and specifications subject to change without notice.







JOB NAME:

CAT#:



TYPE:

DIMENSIONS

4FT Dimensions



8FT Dimensions



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: L66R 48 LED 24 DMV WH S5 30 EM HC301WH P11

LED

1. SERIES	2. LENGTH	3. GEAR	4. LIGHT DISTRIBUTION	5. WATTAGE/LUMENS	6. DRIVER	7. FINISH
L66R¹ Regular Recessed Lay-in	48¹ 48" long 96¹ 96" long	LED	Blank Downlight std. U Uplight 1U2D Up and Downlight	Up or Down Only 4 ft. 24 24W 2900 Lumens 36 36W 4300 Lumens 48 48W 5800 Lumens	DMV 120-277V Multivolt Dimmable SDMV Step dimming Multivolt DHV 347-480VAC 0-10V Dimming D347V 347VAC 0-10V Dimming TDMV Triac Dimming 120-277VAC D120 Triac Dimming 120VAC D277 Triac Dimming 277VAC	WH Matte White SL Silver BK Matte Black BZ Bronze IN Iron
L66RF Recessed w/ Flange				8 ft. 72 72W 8600 Lumens 96 96W 11500 Lumens		
L66RR Recessed w/ 1/2" Flange for Drywall				Up/Down 4 ft. 24 24W 1000U-1900D 36 36W 1400U-2900D 48 48W 1900U-3800D 57 57W 2300U-4600D 72 72W 2900U-5700D		
L66S Surface Mounted				8 ft. 48 48W 1900U-3800D 72 72W 2900U-5700D 96 96W 3800U-7700D 108 108W 4300U-8600D 114 114W 4600U-9500D		
L66W Wall Mounted						
L66P Pendant Mounted						

8. LENS MATERIAL	9. COLOR TEMP	10. REFLECTOR(O) ³	11. EMERGENCY(O) ³	12. CABLE(O) ³
S.5 Specular Parabolic Louver (1/2"x1/2"x3/8")	30 3000K 35 3500K 40 4000K 50 5000K	Blank Standard WW Wall Wash M35 Assymetrical reflector for wall wash	EM Emergency Battery Pack 10W ~ 1700 lumens EM5 Emergency Battery Pack 5W ~ 850 Lumens	HC301WH 4' cable kit with white canopy HC301WH5W 4' cable kit + power feed 0-10V dimming Cable incl. w/white canopy (5 wire) HC302WH 12' cable kit with white canopy HC302WH5W 12' cable kit + power feed; 0-10V dimming Cable incl. w/white canopy (5 wire) HC401WH Cable kit with 4' cable & 3 wire power feed/cable incl. and white canopy 2SCS24WH Two stem kits w/24" stem canopy & mount hardware for 4 ft. fixture
SF Snap-in Frosted Lens -85% Transmission				
LV Baffled Louver				

13. PLUG IN(O) ³	14. CONFIGURATION
PI1 3 wire harness, including white, black and green PI2 4 wire harness, including white, black, green and blue for emergency backup PI3D 5 wire harness, including white, black, green, violet and gray	BLANK Individual -B Beginner Run -E Ender Run -J Joiner

NOTES

Custom louvers available in any cell configuration. Consult factory for additional information.
¹4 Recessed grid fixtures will be 1-2" shorter than specified length
²Only available for downlight side of fixture
³O is Optional



Dimensions and specifications subject to change without notice.