



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Premium surface mounted deep cell parabolic fixture designed for maximum efficiency and visual comfort. Ideal for commercial and industrial buildings requiring general illumination with surface mount configurations and low glare.

- P3 Technology - Post Powder Paint
- > 90% reflectivity
- Corrosion and scratch resistant
- Smooth edges for easy handling
- Clean appearance with no exposed fasteners
- Low iridescent louver is maintenance free semi-specular anodized aluminum
- Louver hinges and latches from either side
- Black reveal provides gap free floating louver appearance
- Various cell configurations available
- UL listed for damp location

Housing is die-formed from cold rolled steel. A framed parabolic troffer offering improved photometrics over our standard welded surface parabolic fixture. Finish is high reflectance P3 - Post Powder Paint. Precision formed anodized semi-specular aluminum louver. Standard nominal 3" deep cell louvers are manufactured using interlocked construction and mitred corners. Louver hinges from either side. Latches use a positive locking cam action and come with matching finish. A protective film is provided to protect the and fixture from construction dust.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.



FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: SPR 14 2 17 8 LEDL7W 830 OL

SPR

1. SERIES	2. SIZE	3. # OF LAMPS	3. LAMP TYPE	4. LOUVERS	6. LAMP WATTAGE (O) ¹
SPR	14 1X4	2 2 Lamps	17 24 inch T8	1X4	T8 Options
	22 2x2	3 3 Lamps	32 48 inch T8	8 8 cell (1x8 pattern) Semi-specular, 3 in. nominal	2 ft.
	24 2x4	4 4 Lamps	54 46 inch T5HO	2X2	LEDL7W 7 Watts 950 Lumens <u>Keystone</u>
				9 9 cell (3x3 pattern) Semi-specular, 3 in. nominal	LEDL9W 9 Watts 1050 Lumens
				12 12 cell (4x3 pattern) Semi-specular, 3 in. nominal	4 ft.
				16 16 cell (4x4 pattern) Semi-specular, 3 in. nominal	LEDL12W 12.5 Watts 1750 Lumens <u>Keystone</u>
				2X4	LEDL15W 15 Watts 1740 Lumens
				12 12 cell (2x6 pattern) Semi-specular, 3 in. nominal	LEDL18W* 18 Watts 2500 Lumens
				16 16 cell (2x8 pattern) Semi-specular, 3 in. nominal	T5 Options
				18 18 cell (3x6 pattern) Semi-specular, 3 in. nominal	LEDL25W 25 Watts 3300 Lumens
				24 24 cell (4x6 pattern) Semi-specular, 3 in. nominal	
				32 32 cell (4x8 pattern) Semi-specular, 3 in. nominal	

*Premium lamp option

5. COLOR TEMP	6. LAMP BRAND	7. OVERLAY (O) ¹	8. WHIP (O) ¹	9. INVERTER (O) ¹
830 3000K	Blank House Brand Lamp (Savegreen)	OL Frosted Overlay Behind Louver	WP 6' Whip 3 Wire	INV5 5W Integrated Inverter
835 3500K				
840 4000K	KEY Keystone Brand			
850 5000K		JAM James Brand**		

**Special Order

Notes:
(O) is optional

Dimensions and specifications subject to change without notice.

