

**JOB NAME:**
**CAT#:**
**TYPE:**

## APPLICATIONS

The linear 4x4 pendant or surface mounted fixture is for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas. The 4x4 Series fixtures can be installed individually or in group patterns.

- Fixtures can be surface mounted to the ceiling or pendant hung by stem, cable or wall mounted
- Accepts various lenses or louvers
- 6' and 8' units have a steel mullion to join two individual diffusers
- Optional welded light-leak hinges are available on ends
- Alignment brackets are available for continuous row mounting
- UL listed for damp location



Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide some uplight for ceiling illumination.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

## FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- $L_{70} > 50,000$  hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

## DIMENSIONS

4"W x 4"H x fixture length

### Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.mobern.com/EZLEDemergency](http://www.mobern.com/EZLEDemergency).

### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Dimensions and specifications subject to change without notice.





**JOB NAME:**

**CAT#:**

**TYPE:**

**ORDERING**

EXAMPLE: L44 R 1 17 LEDL7W MW 30 HC301WH

**L44**

1. SERIES	2. MOUNTING	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. FINISH
<b>L44</b>	<b>R</b> Regular recess lay-in	<b>1</b> 1 Lamp	<b>17</b> 24 inch T8	<b>T8 OPTIONS</b>  <b>2 ft.</b> <b>LEDL7W</b> 7 Watts 950 Lumens <a href="#">Keystone</a> <b>LEDL15W</b> 9 Watts 1050 Lumens  <b>3 ft.</b> <b>LEDL12W</b> 12 Watts 1250 Lumens <a href="#">Keystone</a> <b>LEDL12W</b> 12.5 Watts 1750 Lumens <a href="#">Keystone</a> <b>LEDL15W</b> 15 Watts 1740 Lumens <b>LEDL18W</b> 18 Watts 2500 Lumens  <b>T5 Options</b> <b>LEDL25W</b> 25 Watts 3300 Lumens	<b>Blank</b> For Recessed <b>WH</b> White <b>SL</b> Silver <b>BK</b> Black <b>BZ</b> Bronze <b>IN</b> Iron
	<b>RF</b> Recessed with flange <sup>1</sup>	<b>2</b> 2 Lamps	<b>25</b> 36 inch T8		
	<b>RR</b> Recessed for dry wall 1/2"		<b>25 TAN</b> 72 inch T8 -2-36"		
	<b>S</b> Surface/pendant (direct only)		<b>32</b> 48 inch T8		
	<b>SI</b> Surface/pendant (indirect only)		<b>32TAN</b> 96 inch T8 -2-48		
	<b>SDI</b> Surface/pendant direct w/indirect slots)		<b>54<sup>2</sup></b> 46 inch T5HO		
	<b>WI</b> Wall mount indirect only				
	<b>WDI</b> Wall mount direct w/indirect slots				
	<b>W</b> Wall mount direct only				

7. LENS	8. COLOR TEMP	9. LAMP BRAND	10. REFLECTOR(O) <sup>4</sup>	11. HANGING KIT(O) <sup>4</sup>
<b>MW</b> Matte White lens (std) .100 thick lens	<b>30</b> 3000K <b>35</b> 3500K	<b>Blank</b> House Brand <b>KEY</b> Keystone Brand <b>JAM</b> James Brand <sup>3</sup>	<b>Blank</b> Standard <b>WW</b> Wall Wash	<b>HC301WH</b> Cable kit with 4' Cable + power feed cable incl. with white canopy <b>HC302WH</b> Cable kit with 12' Cable +power feed cable incl. with white canopy
<b>S5</b> Specular Parabolic Louver (1/2"x1/2"x3/8")	<b>40</b> 4000K <b>50</b> 5000K			
<b>SF</b> Snap-in Frosted Lens -85% Transmission				
<b>LV</b> Baffled Louver				
<b>A</b> Prismatic Acrylic #12 pattern				

12. PLUG IN(O) <sup>4</sup>	13. INVERTER(O) <sup>4</sup>
<b>PI1</b> 3 wire harness, including white, black and green	<b>INV5</b> 5W Integrated Inverter
<b>PI2</b> 4 wire harness, including white, black, green and blue for emergency backup	
<b>PI3D</b> 5 wire harness, including white, black, green, violet and gray	

**NOTES:**

- <sup>1</sup>RF for sheetrock installation
- <sup>2</sup>Only Available in 840 & 850
- <sup>3</sup>Special Order
- <sup>4</sup>O is optional



Dimensions and specifications subject to change without notice.