



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Specification grade, modular linear lighting luminaire in a geometric 6 inch shape. For use in indoor applications where individual or continuous lighting is desired for general or perimeter lighting applications. The L66 LED Series is available in surface, pendant (suspended) or recessed. Recessed L66 Series are available for T-bar installation without a flange or for flanged construction for sheetrock installation. Pendant and surface mount configurations allow direct light only. Pendant mounted fixtures can be used with cable kits or rigid stem kits specified separately. Surface and pendant fixtures can be painted in a variety of finishes for the right look for your application.



Housing is die-formed and welded of heavy gauge cold rolled steel. Knockouts on the ends allow continuous wireway mounting. Fixtures can be hung in various types of recessed ceilings. Leveling lugs are available to support regular recess units. All metal parts are cleaned and treated with a three-stage phosphate coating. These are electrostatically sprayed with high quality white baking enamel providing a minimum of 67% reflectivity.



FEATURES & BENEFITS

- 6.0W x 6.0H (See Dimensions)
- Various lenses lie on the side flanges
- 6' and 8' units have a steel mullion to join two individual diffusers
- Baffled louver is available to shield glare
- Recessed versions are all IC Rated (L66R,L66RF,L66RR)
- cETL_{us} listed

DIMENSIONS



Baffled Louver (BL)

Dimensions and specifications subject to change without notice.







JOB NAME:

CAT#:



TYPE:

DIMENSIONS

4FT Dimensions



8FT Dimensions



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: L66R 48 LED 24 DMV WH S5 30 EM HC301WH P11

LED

1. SERIES	2. LENGTH	3. GEAR	4. LIGHT DISTRIBUTION	5. WATTAGE/LUMENS	6. DRIVER	7. FINISH
L66R Regular Recessed Lay-in	48' 48" long	LED	Blank Downlight std.	Up or Down Only	DMV 120-277V Multivolt 0-10V Dimmable	WH Matte White
	96 96" long		U Uplight			
L66RF Recessed w/ Flange			1U2D Up and Downlight	24 24W 2400 Lumens	SDMV Step dimming Multivolt	BK Matte Black
				35 35W 3400 Lumens		
L66RR Recessed w/ 1/2" Flange for Drywall				57 57W 5400 Lumens	DHV 347-480VAC 0-10V Dimming	IN Iron
				72 72W 7000 Lumens		
L66S Surface Mounted				97 97W 9600 Lumens	D347V 347VAC 0-10V Dimming	
L66W Wall Mounted				114 114W 10800 Lumens		TDMV Triac Dimming 120-277VAC
L66P Pendant Mounted				Up/Down		
				24 24W 800U-1600D	4 ft.	
				36 36W 1200U-2400D	D277 Triac Dimming 277VAC	
				48 48W 1600U-3200D		
				57 57W 1900U-3800D		
				72 72W 2400U-4800D		
				8 ft.		
				48 48W 1600U-3200D		
				72 72W 2400U-4800D		
				97 97W 3200U-6400D		
				108 108W 3600U-7200D		
				114 114W 3600U-7200D		

8. LENS MATERIAL	9. COLOR TEMP	10. REFLECTOR(O) ³	11. EMERGENCY(O) ³	12. CABLE(O) ³
S5 Specular parabolic louver	30 3000K	Blank Standard	EM Emergency Battery Pack 10W ~ 1700 lumens	HC301WH 4' cable kit with white canopy
	35 3500K			
W5 White cubed acrylic louver	40 4000K	M35 Assymetrical reflector for wall wash	EM5 Emergency Battery Pack 5W ~ 850 Lumens	HC302WH 12' cable kit with white canopy
	50 5000K			
A Prismatic acrylic #12 pattern				HC401WH Cable kit with 4' cable & 3 wire power feed/cable incl. and white canopy
BL Baffled Louver ²				2SCS24WH Two stem kits w/24" stem canopy & mount hardware for 4 ft. fixture
MW Matte white lens				
SF Snap-in Frosted (85% transmission)				

13. PLUG IN(O) ³
P11 3 wire harness, including white, black and green
P12 4 wire harness, including white, black, green and blue for emergency backup
P13D 5 wire harness, including white, black, green, violet and gray

14. CONFIGURATION
BLANK Individual
-B Beginner Run
-E Ender Run
-J Joiner

NOTES

Custom louvers available in any cell configuration. Consult factory for additional information.
¹4 ft. available but not available in recessed
²Only available w/ upright & downlight
³O is Optional

Dimensions and specifications subject to change without notice.

